

**DECLARATION OF PERFORMANCE**  
**Under the CPR EU 305/2011**  
**No. 2023-003 SA34**

1. Unique identification code of the product-type:

**ONDUTISS® STRONG 1300; ONDUTISS® STRONG 1300 TT**

2. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Bituminous underlay for discontinuous roofing**

3. Name, registered trade name or registered trademark and contact address of the manufacturer as required under Article 11(5):

**Onduline SA**  
**24 Quai Gallieni**  
**92 150 Suresnes – France**  
[www.onduline.com](http://www.onduline.com)

4. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

**Not Applicable**

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

**System 3**

6a. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**EN 13859-1: 2010**

Notified Body (NB) : **0071 - LNE, Rue Gaston Boissier, 75724 Paris Cedex 15 – For Initial Type Testing**

7. Declared performances

Characteristics before aging :	Unit	Performance	Tolerance	Harmonized technical specification
Reaction on fire	Class	E	-	EN13859-1 :2010
Resistance to water penetration	Class	W1	-	
Tensile strength along MD /CD	[N/50mm]	730/450	±15%	
Elongation along MD / CD	[%]	35-55/45-65		
Tear resistance along MD /CD	[N]	250/330	±15%	
Flexibility at low temperature	[°C]	-40	-	
Dangerous Substances	-	NPD		
<b>Resistance to artificial aging :</b>				
Tensile strength along MD /CD	[N/50mm]	694/405	±15%	EN13859-1 :2010
Resistance to water penetration	Class	W1	-	

8. Appropriate Technical Documentation and/or Specific Technical documentation : **NO**

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

**Christophe ROHART**  
**R&D Director**

Suresnes, 13/07/2023 ver.1





0071

**ONDULINE SA**

**24, Quai Gallieni – 92 150 Suresnes – France**

**[www.onduline.com](http://www.onduline.com)**

**23**

**DOP N° 2023-003 SA34**

**EN 13859-1: 2010**

**ONDUTISS® STRONG 1300; ONDUTISS®  
STRONG 1300 TT**

**Bituminous underlays for discontinuous roofing**

**Reaction on fire: E**

**Resistance to water penetration :**

- **Before artificial aging : W1**
- **After artificial aging : W1**

**Tensile strength along MD /CD :**

- **Before artificial aging : 730/450 N/5cm**
- **After artificial aging : 694/405 N/5cm**

**Elongation along MD / CD : 35-55/45-65 %**

**Tear resistance along MD /CD : 250/330 N**

**Flexibility at low temperature : -40 °C**

**Dangerous substances : NPD**